

TECHNICAL INFORMATION ENGINEERED WOOD FLOORING

OVERVIEW OF THE RANGE				BASIC	CLASSIC	TRENDTIME				
RANGE				BASIC 11-5	CLASSIC 3060	TRENDTIME 3	TRENDTIME 4	TRENDTIME 6	TRENDTIME 8	TRENDTIME 9
GRADE				NATUR, CLASSIC, RUSTIKAL	SELECT, NATUR, LIVING, RUSTIKAL	LIVING	NATUR, LIVING	LIVING	CLASSIC	CLASSIC
SURFACE FINISH										
PLANK LOOK				1 3-STRIP 2 WIDE PLANK 3 EXTRA-SIZED WIDEPLANK 4 STRIP (HERRINGBONE INSTALLATION) 5 CHEVRON 						
GROOVE PATTERN					4-SIDED MINI BEVEL (M4V)	✓	✓			✓
					4-SIDED BEVEL (4V)	✓	✓	✓	✓	
QUALITY	GUARANTEE				10 YEARS	25 YEARS	25 YEARS	25 YEARS	25 YEARS	25 YEARS
TECHNOLOGY										
FORMAT				(1,2) 2200 X 185 MM (3) 2380 X 233 MM	2200 X 185 MM	570X95 MM	2010X160 MM	2200 X 185 MM	1882X190MM	2380 x 233 MM
PLANK THICKNESS				11,5 MM	13 MM	10,5 MM	13MM	13 MM	14 MM/15 MM	15 MM
COMPOSITION				3-LAYER SANDWICH COMPOSITION	✓	✓	✓	✓	✓	✓
MIDDLE LAYER				SOLID SPRUCE-FIR MIDDLE LAYER	✓	✓	✓	✓	✓	✓
TOP LAYER				CA. 2,5MM	CA. 3,6 MM	CA. 2,5MM	CA. 3,6MM	CA. 3,6MM	CA. 3 MM/4 MM	CA. 3,6MM
SWELL PROTECTION					ALL-ROUND LAMELLA AND TOP LAYER IMPREGNATION	✓	✓	✓	✓	✓
CLICK MECHANISM					AUTOMATIC-CLICK® SYSTEM WITH LONG-SIDE AND END-JOINT LOCKING	✓	✓	✓	✓	✓
					ALLROUND-CLICK® SYSTEM WITHOUT THE NEED FOR LEFT AND RIGHT-HAND TONGUES	✓				
UNDERFLOOR HEATING					SUITABLE FOR INSTALLATION ON UNDERFLOOR HEATING	✓	✓	✓	✓	✓
					INDIVIDUAL LOOK THANKS TO CRAFTSMANSHIP SURFACE TREATMENT				✓	